

# PG

## L2535, L2540, L2540 plus

**FLEXIBLE, MONO PRINTING AT HIGH PERFORMANCE SPEEDS**

The PG L2535, PG L2540 and PG L2540plus are Olivetti's latest A4 Mono Desktop laser printers. Not only they are compact and robust but are also high speed machines delivering jobs quickly and silently with indispensable functions that are ideally suited to individual users and small workgroups.

The PG L2535 reaches printing speeds of 35 A4 pages per minute while the PG L2540 and PG L2540plus print at 40 ppm, respectively. They are all equipped with a standard duplex unit and provide a print resolution of 1,200 dpi and first page-out time of under 7 seconds, but only the PG L2540plus supports Wi-Fi® and Wi-Fi Direct® as standard.

Productivity can be further increased through the addition of optional paper trays, achieving a maximum paper capacity of 850 sheets. With a four-way paper feed system supporting a broad mix of paper types and sizes, versatility is guaranteed!





Flexible paper management



LCD operator panel PG L2540



LED operator panel PG L2535



Compact and easy to manage

## TECHNICAL SPECIFICATIONS

### PG L2535

### PG L2540

### PG L2540plus

#### GENERAL

<b>Type</b>	Desktop printer		
<b>Technology</b>	Monochrome Laser		
<b>Control Panel</b>	LED	2-row rear-lit LCD display	2-row rear-lit LCD display
<b>Printing Speed</b>	35 pages per minute	40 pages per minute	40 pages per minute
<b>Printing Resolution</b>	300 dpi, 600 dpi, 1200 dpi		
<b>Warm-up Time</b>	15 secs or less		
<b>First Page-out Time</b>	Approx. 6.8 secs or less	Approx. 6.4 secs or less	Approx. 6.4 secs or less
<b>Processor</b>	800 MHz		
<b>Memory</b>	Standard 256 MB, Max. 256 MB		
<b>Standard Interfaces</b>	USB 2.0 (Hi-Speed), USB Host Interface, Gigabit Ethernet (10Base-T/100Base-TX/1000 Base-T), Slots for SD/SDHC optional cards	USB 2.0 (Hi-Speed), USB Host Interface, Gigabit Ethernet (10Base-T/100Base-TX/1000 Base-T), Slots for SD/SDHC optional cards	USB 2.0 (Hi-Speed), USB Host Interface, Gigabit Ethernet (10Base-T/100Base-TX/1000 Base-T), Wireless LAN, Slots for SD/SDHC optional cards
<b>Base Unit Dimensions (W x D x H)</b>	375 x 393 x 272		
<b>Base Unit Weight</b>	14 Kg		
<b>Power Supply</b>	AC 220/240 V, 50/60 Hz		
<b>Power Consumption</b>	Printing: 620 W; Standby: 8 W; Sleep: 0.8 W		
<b>Noise Levels (ISO 7779/ISO 9296)</b>			
- Printing	47.9 dB(A) LpA	48.8 dB(A) LpA	48.8 dB(A) LpA
- Standby / Sleep mode	Below measurable levels		
<b>Safety Standards</b>	GS, TUV, EC. These products are manufactured by a company operating in conformity with ISO 9001 Quality Standards and ISO 14001 Environmental Directives		

#### PAPER MANAGEMENT

<b>Paper Input Capacity</b>	Universal bypass 100 sheets - 60-220 g/m <sup>2</sup> - A4, A5, A6, B5, B6, Letter, Legal, Custom (70 x 148 mm - 216 x 356 mm); Universal paper tray 250 sheets - 60-163 g/m <sup>2</sup> - A4, A5, A6, B5, Letter, Legal, Custom (105 x 148 - 216 x 356 mm). Max paper capacity with options: 850 A4 sheets		
<b>Standard Duplex mode</b>	60 - 163 g/m <sup>2</sup> ; A4, A5, B5, Letter, Legal		
<b>Paper Output Capacity</b>	Max 250 sheets face down		

#### PRINTING FUNCTIONS

<b>Emulations</b>	PCL 6 (PCL 5e/PCL-XL), PostScript 3 (KPDL 3), XPS/Open XPS		
<b>Operating Systems</b>	All current Windows operating systems, Mac OS X Version 10.5 or later, UNIX, LINUX and other systems		
<b>Fonts/Barcodes</b>	93 scalable fonts for PCL6 / KPD3, 8 fonts for Windows Vista, 1 Bitmap font, 45 barcode types (e.g. EAN 8, EAN 13) with automatic generation of checksums and support for PDF417 two-dimensional barcodes (PCL and other barcodes available as options)		
<b>Integrated Accounting</b>	N/A	20 department codes	20 department codes

#### CONSUMABLES

<b>Black Toner Cartridge Capacity according to ISO 19752 (B1235)</b>	N/A	Up to 7,200 A4 pages Initial supply up to 3,600 A4 pages	Up to 7,200 A4 pages Initial supply up to 3,600 A4 pages
<b>Black Toner Cartridge Capacity according to ISO 19752 (B1233)</b>	Up to 3,000 A4 pages Initial supply up to 1,000 A4 pages	N/A	N/A
<b>Maintenance Kit (B1236)</b>	Up to 100,000 A4 pages		

#### OPTIONS

<b>Paper Tray (B3415)</b>	PF-1100 (Max 2 trays) : 250 sheets; 60-163 g/m <sup>2</sup> ; A4, A5, A6, Letter, Legal, Custom (105 x 148 mm - 216 x 356 mm) Thin Print		
<b>UG-33 (B8403)</b>	protocol support module		
<b>USB IC Card Reader + Card Authentication Kit B- (B8237)</b>	N/A	Various types of identification supported	Various types of identification supported
<b>PCL Barcode Flash 3.0 (B4998)</b>	Extends printable barcodes available		

Performance relates to use of the product under optimal conditions. Right reserved to modify technical specifications. Registered trademarks are the property of their respective owners. PG L2535/PG L2540/PG L2540plus are distributed by Olivetti S.p.A. (04/2021)

